

# Decorock Exterior Surface Sealer

## Product Data Sheet and Performance Properties

### PRODUCT DESCRIPTION

**Decorock Sealer** is a Low VOC Acrylic Sealer used for exterior surface applications. **Decorock Sealer** is a multi-use product designed to create a tough and durable finish by sealing and protecting concrete, stone, pavers and decorative concrete finishes. It is formulated to emphasize the contrasts and colours of the finish leaving a scuff and chemically resistant surface by penetrating the exposed layer of the substrate and binding to the cured matrix.

### SURFACE PREPARATION

Make sure the substrate is clean, dry, and free of efflorescence, oil, paint, loose material or any other foreign matter. Concrete should be fully cured (28 days) for best results.

Moisture or moisture emitting surfaces may form a sporadic haze within the coating that may disappear over time. Avoid this by ensuring concrete is fully cured or that the coating is applied in a warm environment. Prior sealed surfaced should be lightly sanded to remove loose/crystallized remains.

### APPLICATION & COVERAGE

Be sure to apply **Decorock Sealer** in temperatures above 8°C. Test **Decorock Sealer** in an inconspicuous at first. Let it dry for 4 hours and check to see that you have achieved desired results.

Apply either; 1 generous coat or in two thin coats. **Decorock Sealer** can be applied with a roller or a spray-pump applicator.

Coverage rate may vary depending on substrate, substrate conditions and application method.

Theoretically, **Decorock Sealer** has a coverage rate of 160 - 180 ft<sup>2</sup>/gallon.

### DRYING TIME

SUBSTRATE TEMPERATURE	HARD DRY	RE-COAT
25°C	15 MINS	30 MINS
15°C	30 MINS	60 MINS
8°C	1 HOUR	4 HOUR

### PRODUCT INFORMATION

GENERIC TYPE	ACRYLIC
PIGMENT TYPE	NON-PIGMENTED
COLOUR	CLEAR
BASES	N/A
FINISH	MID TO HIGH SHINE
AVERAGE VOLUME SOLIDS	18%
AVERAGE WEIGHT SOLIDS	22%
RECOMMENDED FILM THICKNESS	WET: 1.8 – 6.4 DRY: 1.0 – 4.0
VISCOSITY	18 – 20 SECS; #2 ZAHN CUP
V.O.C AS APPLIED	<475 GM/LIT (3.9 LB/USG)
CLEAN UP	XYLENE
FLASH POINT	-7°C

## **STORAGE & HANDLING**

Keep containers tightly sealed and protected when not in use. Store in a cool, dry and well ventilated area. Keep out of direct sunlight.

## **SAFETY PRECAUTIONS**

### **KEEP AWAY FROM CHILDREN**

### **DO NOT LEAVE PAIL OPEN WITHOUT ADULT SUPERVISION**

This product is for exterior use only. Refer to Material Safety Data Sheets (MSDS) for Health & Safety information.

**PACKAGING SIZE:** 5 USG Pails

## **WARRANTY DISCLAIMER**

Decorock uses quality products. In the event that this product is defective or in any way unsuitable for the application it is sold, we will replace the product free of charge. The warranty provided with this data sheet is the only warranty or guarantee of quality made in respect to the product by Decorock Inc. By purchasing this product, the customer accepts this warranty in lieu of all others, and waives all claims to any other remedy arising from any warranty or guarantee of quality, whether such warranty or guarantee of quality was made expressly to the customer or implied by any applicable law.